

AMERICAN WIRE WHEELS CLASSIC 100 SPOKE WHEELS FOR 1999 & EARLIER AND 2000 & LATER



SPECS: Chrome plated steel rims, chrome plated steel spokes & chrome plated nipples. Chrome plated billet aluminum hubs. All internal bearings, races, seals and spacers are installed and all bearing end-play is set at factory. **SKINNY:** 87 Years experience building custom wire spoke laced wheels. CNC milled hubs and CNC dimpled rims for precise fit, strength & trueness. All 16" and 18" wheels are factory sealed to run tubeless tires. All tubeless designed wheels come complete with valve stems. The 100 spoke wheels use oversized .203" wire swaged to .156" in a cross laced pattern. OEM spec chrome plating, all in-house facilities. **SOLD EACH**

PART NO.	SIZE	APPLICATION
----------	------	-------------

FRONT 1999 & EARLIER - TAPERED BEARINGS

36-697	19" x 2.5"	FXD, FXR, XL, 1984 thru 1999. Narrow dual disc.
36-757	21" x 3"	Custom application ONLY (stainless). Single disc.

REAR 1999 & EARLIER - TAPERED BEARINGS

36-759	16" x 3.5"	FLT, FLH, belt drive, 1984 thru 1999.
36-760	16" x 5.00"	Custom application ONLY.

FRONT 2000 & LATER - SEALED BEARINGS

36-768	21" x 2.15"	2000 Thru 2003 FXD, FXR, 2000 & later XL. Narrow dual disc.
--------	-------------	---

REAR 2000 & LATER - SEALED BEARINGS

36-773	16" x 3.5"	2002 & Later FLH, FLT, belt drive, with 1" dia. axle.
36-774	16" x 5.00"	Custom application ONLY. Sealed bearing.
36-775	18" x 5.50"	Custom application ONLY. Sealed bearing.

5

AMERICAN WIRE WHEELS 100 SPOKE RADIAL WHEELS FOR 1999 & EARLIER AND 2000 & LATER



SPECS: Chrome plated steel rims, polished stainless steel spokes & chrome plated nipples. Chrome plated billet aluminum hubs. All internal bearings, races, seals and spacers are installed and all bearing end-play is set at factory. **SKINNY:** 87 Years experience building custom wire spoke laced wheels. CNC milled hubs and CNC dimpled rims for precise fit, strength & trueness. All 16" and 18" wheels are factory sealed to run tubeless tires. All tubeless designed wheels come complete with valve stems. The 100 spoke radial wheels use oversized .203" wire swaged to .156" in a radial (non-crossing) laced pattern. OEM spec chrome plating, all in-house facilities. **SOLD EACH**

PART NO.	SIZE	APPLICATION
----------	------	-------------

REAR 1999 & EARLIER - TAPERED BEARINGS

36-791	16" x 5.00"	Custom application ONLY.
--------	-------------	--------------------------

FRONT 2000 & LATER - SEALED BEARINGS

36-795	16" x 3.5"	2000 Thru 2003 FLSTS (Springer®). Single disc.
36-797	19" x 2.5"	2000 thru 2004 FXD with 1" dia. axle. Narrow dual disc.

REAR 2000 & LATER - SEALED BEARINGS

36-884	16" x 5.00"	Custom application ONLY. Sealed bearing.
36-787	18" x 8.50"	Custom application ONLY. 3/4" Sealed bearing.

HALLCRAFT QUALITY WHEEL ACCESSORIES

Hallcraft, the undisputed industry leader in wire wheel applications now has available wire wheels for 2000 H-D® models. These wheels use a 1" axle and come ready to install using stock H-D® bearings. Like all Hallcraft's wheels these are guaranteed 100% tubeless and are factory balanced featuring Hallcraft's exclusive internal balancing system developed by Balance Master™ eliminating the need for unsightly external wheel weights. These awesome wheels are triple chrome show chrome plated in Hallcraft's state of the art chrome plating facility.



OPTIONAL WHEEL ACCESSORIES FOR 2000 APPLICATIONS

90-647 1" Wide spacer for wide tire/pulley mounting. **SOLD EACH**
90-649 Brake flange for Road King® Rear wheel application.