

A

EXHAUST INSULATING WRAP

A. EXHAUST INSULATING WRAP

Increases horsepower and fuel efficiency by maintaining hotter exhaust gases that exit faster through decreased density. Wraps withstand continuous heat up to 2000° F.

- 64-110 Brown, 2" x 50' Exhaust Wrap SOLD EACH
- 64-111 Black, 2" x 50' Exhaust Wrap
- 64-112 Copper, 2" x 50' Exhaust Wrap

B

B. SNAP STRAP KIT

Stainless steel straps offer quick and clean looking installation. Just insert end and pull to tighten.

- 66-110 Snap strap kit, 12 pack of 9" straps. SOLD EACH

C. STAINLESS STEEL SAFETY WIRE NEW!

Wire comes in a handy 1 pound dispensing canister. Meets ASTM A580 chemistry. SOLD AS ROLL

- ★18-790 22 gage safety wire, .025" dia.; aprox 595 ft. per roll.
- ★18-791 20 gage safety wire, .032" dia.; aprox 362 ft. per roll.
- ★18-792 18 gage safety wire, .041" dia.; aprox 221 ft per roll.

C

D. SAFETY WIRE TWISTER PLIERS NEW!

Reversible safety wire pliers provide right and left twist capability. Designed for wire sizes .020" - .041" dia.

- ★97-201 Safety wire pliers. SOLD AS EACH

E. FIRE RING FOR SHOVEL

This fire ring is a one piece copper & fiber exhaust port gasket shaped like the exhaust port flange. Copper fire ring helps prevent burn out.

- 78-143 SOLD EACH

10**D**

F. EXHAUST POWER CONES

Steel cones are CNC machined and require no special tool or alteration to install between the head and head pipe. Can be welded in place to help stop any rattles or leaks. Should be used on straight pipes to increase low end torque. Helps eliminate flat spots and increase back pressure.

- 64-477 Fits Evolution® and Twin Cam®. SOLD AS PAIR
- 64-480 Fits Shovelhead.

F